

Capacitors > Ceramic Trimmer Capacitors














How to check EU RoHS Compliance of Our Products is [here](#).

Product Lifecycle Stage	in Production
Recommended Rank	Preferred

Specifications

Details

Global Part Number	TZB4Z030AB10R01
Previous Part Number	
Cmin. (max.)	1.4pF
Cmax.	3.0pF +50/-0%
TC	NP0±200ppm/°C
Q	300min. at 1MHz, Cmax.
Rated Voltage	100Vdc
Withstanding Voltage	220Vdc
Insulation Resistance (min.)	10000M ohm
Torque	1.5 to 9.8mNm
Operating Temperature Range	-25 to +85°C
Stator/Case Color	Brown
Adjustment Direction	Top
Soldering Method	Flow/Reflow
Height	3mm ±0.2
Mass	0.15g

-  [Part Numbering](#)
-  [Appearance](#)
-  [Dimensions](#)
-  [Features and Applications](#)
-  [Construction](#)
-  [Land Pattern](#)
-  [Taping Dimensions](#)
-  [Reel Dimensions](#)
-  [Notice \(Storage and operating condition\)](#)
-  [Notice \(Soldering and Mounting\)](#)
-  [Notice \(Handling\)](#)
-  [Notice \(Other\)](#)
-  [Soldering Profile](#)

Minimum Quantity

180mm Paper Tape	
180mm Embossed Tape	
330mm Paper Tape	
330mm Embossed Tape	2500
Bulk Case	
Bulk(Bag)	
Ammo Pack	

320Reel	
Magazine	
Box	

Please approve our product specifications or to transact the approval sheet for product specifications before ordering.

Please read rating and !Cautions first.

Product specifications in this catalog are as of January 2014

Please make sure to read the Murata's [Product Policy](#) ,too.

All products and company names herein are trademarks or registered trademarks of their respective owners.

UP 

| [Site Map](#) | [History](#) | [Terms of use](#) | [Privacy Policy](#) |

All Rights Reserved, Copyright© Murata Manufacturing Co., Ltd.